

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T1-ITRd / TFLH1-ITRd / Mini 650-ITRd				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	0,65	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	0,65	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,52	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0075	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0075	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0067	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	no
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T1-FlexiSmart / TFLH1-FlexiSmart / Mini 650-FlexiSmart S650 -Smart heat				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	0,65	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	0,65	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,52	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0001	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	Mini 650-FlexiSmartPro / S-650 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	0,65	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	0,65	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,52	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l,max}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l,min}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l,SB}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	Mini 650 / S650-Ohne Regler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nennwärmeleistung	P_{nom}	0,65	kW	manual heat charge control, with integrated thermostat	N/A
Mindestwärmeleistung (Richtwert)	P_{min}	0,65	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximale kontinuierlicher Wärmeleistung	$P_{max,c}$	0,52	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Hilfsstromverbrauch				fan assisted heat output	N/A
Bei Nennwärmeleistung	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
Bei Mindestwärmeleistung	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
Im Bereitschaftszustand	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	Mini 650 / S650-Funk X3D				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nennwärmeleistung	P_{nom}	0,65	kW	manual heat charge control, with integrated thermostat	N/A
Mindestwärmeleistung (Richtwert)	P_{min}	0,65	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximale kontinuierlicher Wärmeleistung	$P_{max,c}$	0,52	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Hilfsstromverbrauch				fan assisted heat output	N/A
Bei Nennwärmeleistung	$e_{l,max}$	0,005	kW	Type of heat output/room temperature control (select one)	
Bei Mindestwärmeleistung	$e_{l,min}$	0,005	kW	single stage heat output and no room temperature control	yes
Im Bereitschaftszustand	$e_{l,SB}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
Other control options (multiple selections possible)					
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T2-FlexiSmart / TFLH2-FlexiSmart / COMPACT 1000-FlexiSmart M1000-SmartHeat				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,90	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0001	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	COMPACT 1000 / M1000-Ohne Regler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,90	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	COMPACT 1000 / M1000-Funk X3D				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,90	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,005	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,005	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	M-1000 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,900	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T3-ITRd / TFLH3-ITRd / COMPACT 1300-ITRd				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,30	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,30	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,092	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0075	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0075	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0067	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	no
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):						T3-FlexiSmart / TFLH3-FlexiSmart / COMPACT 1300-FlexiSmart M1300-Smart heat					
Item	Symbol	Value	Unit		Item	Unit					
Heat output				Type of heat input, for electric storage local space heaters only (select one)							
Nominal heat output	P_{nom}	1,30	kW		manual heat charge control, with integrated thermostat	N/A					
Minimum heat output (indicative)	P_{min}	1,30	kW		manual heat charge control with room and/or outdoor temperature feedback	N/A					
Maximum continuous heat output	$P_{max,c}$	1,092	kW		electronic heat charge control with room and/or outdoor temperature feedback	N/A					
Auxiliary electricity consumption				fan assisted heat output							
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)							
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control				no			
In standby mode	$e_{l_{SB}}$	0,0001	kW	Two or more manual stages, no room temperature control				no			
				with mechanic thermostat room temperature control				no			
				with electronic room temperature control				no			
				electronic room temperature control plus day timer				no			
				electronic room temperature control plus week timer				yes			
				Other control options (multiple selections possible)							
				room temperature control, with presence detection				no			
				room temperature control, with open window detection				yes			
				with distance control option				yes			
				with adaptive start control				yes			
				with working time limitation				no			
				with black bulb sensor				no			
Contact details		Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany									

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	COMPACT 1300-FlexiSmartPro / M-1000 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,30	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,30	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,092	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	COMPACT 1300 / M1300-Ohne Regler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,30	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,30	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,092	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	COMPACT 1300 / M1300-Funk X3D				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,30	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,30	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,092	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,005	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,005	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SmartHeater 1300 FlexiSmart Pro-Regler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,30	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,30	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,720	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):						T5-FlexiSmart / TFLH5-FlexiSmart/ MIDI 1500-FlexiSmart L1500-SmartHeat					
Item	Symbol	Value	Unit		Item	Unit					
Heat output				Type of heat input, for electric storage local space heaters only (select one)							
Nominal heat output	P_{nom}	1,50	kW		manual heat charge control, with integrated thermostat	N/A					
Minimum heat output (indicative)	P_{min}	1,50	kW		manual heat charge control with room and/or outdoor temperature feedback	N/A					
Maximum continuous heat output	$P_{max,c}$	1,35	kW		electronic heat charge control with room and/or outdoor temperature feedback	N/A					
Auxiliary electricity consumption				fan assisted heat output							
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)							
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control				no			
In standby mode	$e_{l_{SB}}$	0,0001	kW	Two or more manual stages, no room temperature control				no			
				with mechanic thermostat room temperature control				no			
				with electronic room temperature control				no			
				electronic room temperature control plus day timer				no			
				electronic room temperature control plus week timer				yes			
				Other control options (multiple selections possible)							
				room temperature control, with presence detection				no			
				room temperature control, with open window detection				yes			
				with distance control option				yes			
				with adaptive start control				yes			
				with working time limitation				no			
				with black bulb sensor				no			
Contact details		Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany									

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	L1500-Ohne Regler / MIDI 1500 - ohne Regler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,50	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,50	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,35	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	L1500-Funk X3D / MIDI 1500 mit Funkempfänger X3D				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,50	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,50	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,35	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,005	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,005	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	L-1500 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,50	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,50	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,350	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0001	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T5-ITRd / TFLH5-ITRd / MIDI 1950-ITRd				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,95	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,95	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,796	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0075	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0075	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0067	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	no
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T5-FlexiSmart / TFLH5-FlexiSmart/ MIDI 1950-FlexiSmart L1950-smart heat				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,95	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,95	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,796	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0001	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	MIDI 1950-FlexiSmartPro / L-1950 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,95	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,95	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,796	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0001	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	MIDI 1950 / L1950-Ohne Regler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,95	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,95	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,796	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	MIDI 1950 / L1950-Funk X3D				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,95	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,95	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,796	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,005	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,005	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T6-FlexiSmart / TFLH6-FlexiSmart / MAXI 2000-FlexiSmart XL2000-smart heat				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,80	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l,max}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l,min}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l,SB}$	0,0001	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	XL2000-OhneRegler / MAXI 2000 - ohne Regler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,80	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	XL2000-Funk X3D / MAXI 2000 mit Funkempfänger X3D				
Angabe	Symbol	Wert	Einheit	Angabe	Einheit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,80	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,005	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,005	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	XL-2000 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,80	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T7-ITRd / TFLH7-ITRd / MAXI 2450-ITRd				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,45	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,45	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	2,00	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0075	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0075	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0067	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	no
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T7-FlexiSmart / TFLH7-FlexiSmart / MAXI 2450-FlexiSmart XL2450-smart heat				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,45	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,45	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	2,00	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l,max}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l,min}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l,SB}$	0,0001	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	MAXI 2450-FlexiSmartPro / XL-2500 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,45	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,45	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	2,00	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	MAXI 2450 / XL2450-OhneRegler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,45	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,45	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	2,00	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	MAXI 2450 / XL2450-Funk X3D				
Angabe	Symbol	Wert	Einheit	Angabe	Einheit
Heat output			Type of heat input, for electric storage local space heaters only (select one)		
Nominal heat output	P_{nom}	2,45	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,45	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	2,00	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,005	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,005	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T10-ITRd / TFLH10-ITRd / SLIM TALL 1600-ITRd				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,60	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,60	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,87	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0075	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0075	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0067	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	no
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T10-FlexiSmart / TFLH10-FlexiSmart / SLIM TALL 1600-FlexiSmart V1600-smart heat				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,60	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,60	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,87	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0001	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM TALL 1600-FlexiSmartPro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,60	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,60	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,87	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM TALL 1600-FlexiSmartPro / V-1600 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,60	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,60	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,87	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM TALL 1600 / V1600-Ohne Regler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,60	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,60	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,87	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM TALL 1600 / V1600-Funk X3D				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,60	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,60	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	0,87	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,005	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,005	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T12-ITRd / TFLH12-ITRd / SLIM 1200-ITRd				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,20	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,20	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,057	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0075	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0075	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0067	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	no
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s): T12-FlexiSmart / TFLH12-FlexiSmart / SLIM 1200-FlexiSmart H1200-mart heat					
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,20	kW	manuelle Regelung der Wärmezufuhr mit integriertem Thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,20	kW	manuelle Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	N/A
Maximum continuous heat output	$P_{max,c}$	1,057	kW	elektronische Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	N/A
Auxiliary electricity consumption				Wärmeabgabe mit Gebläseunterstützung	N/A
At nominal heat output	$e_{l,max}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l,min}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l,SB}$	0,0001	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM 1200-FlexiSmartPro / H-1200 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,20	kW	manuelle Regelung der Wärmezufuhr mit integriertem Thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,20	kW	manuelle Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	N/A
Maximum continuous heat output	$P_{max,c}$	1,057	kW	elektronische Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	N/A
Auxiliary electricity consumption				Wärmeabgabe mit Gebläseunterstützung	N/A
At nominal heat output	$e_{l,max}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l,min}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l,SB}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM 1200 / H1200-OhneRegler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,20	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,20	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,057	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM 1200 / H1200-Funk X3D				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,20	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,20	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,057	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,005	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,005	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T13-ITRd / TFLH13-ITRd / SLIM 1600-ITRd				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,60	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,60	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,26	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l,max}$	0,0075	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l,min}$	0,0075	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l,SB}$	0,0067	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	no
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):						T13-FlexiSmart / TFLH13-FlexiSmart / SLIM 1600-FlexiSmart H1600-smart heat					
Item	Symbol	Value	Unit		Item	Unit					
Heat output				Type of heat input, for electric storage local space heaters only (select one)							
Nominal heat output	P_{nom}	1,60	kW		manuelle Regelung der Wärmezufuhr mit integriertem Thermostat	N/A					
Minimum heat output (indicative)	P_{min}	1,60	kW		manuelle Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	N/A					
Maximum continuous heat output	$P_{max,c}$	1,26	kW		elektronische Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	N/A					
Auxiliary electricity consumption				Wärmeabgabe mit Gebläseunterstützung							
At nominal heat output	$e_{l,max}$	0,00049	kW	Type of heat output/room temperature control (select one)							
At minimum heat output	$e_{l,min}$	0,0005	kW	single stage heat output and no room temperature control					no		
In standby mode	$e_{l,SB}$	0,0001	kW	Two or more manual stages, no room temperature control					no		
				with mechanic thermostat room temperature control					no		
				with electronic room temperature control					no		
				electronic room temperature control plus day timer					no		
				electronic room temperature control plus week timer					yes		
				Other control options (multiple selections possible)							
				room temperature control, with presence detection					no		
				room temperature control, with open window detection					yes		
				with distance control option					yes		
				with adaptive start control					yes		
				with working time limitation					no		
				with black bulb sensor					no		
Contact details		Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland									

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM 1600-FlexiSmartPro / H-1600 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,60	kW	manuelle Regelung der Wärmezufuhr mit integriertem Thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,60	kW	manuelle Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	N/A
Maximum continuous heat output	$P_{max,c}$	1,26	kW	elektronische Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	N/A
Auxiliary electricity consumption				Wärmeabgabe mit Gebläseunterstützung	N/A
At nominal heat output	$e_{l,max}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l,min}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l,SB}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM 1600 / H1600-OhneRegler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,60	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,60	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,26	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM 1600 / H1600-Funk X3D				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	1,60	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	1,60	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,26	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	
At nominal heat output	$e_{l_{max}}$	0,005	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,005	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T14-ITRd / TFLH14-ITRd / SLIM 2000-ITRd				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,62	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0075	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0075	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0067	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	no
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Germany				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	T14-FlexiSmart / TFLH14-FlexiSmart / SLIM 2000-FlexiSmart H2000-smart heat				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,62	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0001	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM 2000-FlexiSmartPro / H-2000 Thermalink Pro				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,62	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,00049	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0005	kW	single stage heat output and no room temperature control	no
In standby mode	$e_{l_{SB}}$	0,0004	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	yes
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM 2000 / H2000-OhneRegler				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,62	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,0	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,0	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				

Table 2 of the COMMISSION REGULATION (EU) 2015/1188 as of 28 April 2015

Information requirements for electric local space heaters

Model identifier(s):	SLIM 2000 / H2000-Funk X3D				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	P_{nom}	2,00	kW	manual heat charge control, with integrated thermostat	N/A
Minimum heat output (indicative)	P_{min}	2,00	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A
Maximum continuous heat output	$P_{max,c}$	1,62	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A
Auxiliary electricity consumption				fan assisted heat output	N/A
At nominal heat output	$e_{l_{max}}$	0,005	kW	Type of heat output/room temperature control (select one)	
At minimum heat output	$e_{l_{min}}$	0,005	kW	single stage heat output and no room temperature control	yes
In standby mode	$e_{l_{SB}}$	0,0045	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Thermotec AG Arnsdorf 26 02894 Vierkirchen Deutschland				